

## DECLARATION OF PERFORMANCE No. SP-10/2018-1

- 1. Unique identification code of the product-type: Category I Calcium Silicate bricks SP-10.
- 2. Intended use/es: unprotected masonry (U) to be used in the construction of interior and exterior walls and columns using general purpose mortar or lightweight mortar, in buildings built for various purposes.
- 3. Manufacturer: "Silikatas" AB, Savanorių pr. 124, Vilnius LT-03153, <a href="www.silikatas.lt">www.silikatas.lt</a>, <a href="mailto:info@silikatas.lt">info@silikatas.lt</a>, <a href="mailto:phone.">phone.</a>+370 5 2311850. 4. System of assessment and verification of consistency of performance: 2+
- 5. Harmonised standard: LST EN 771-2:2011+A1:2015 "Specification for masonry units-Part 2:Calcium silicate masonry units".
- 6. Notified body: the state enterprise "Statybos produkcijos sertifikavimo centras", Linkmenų g. 28, Vilnius, identification no. 1397.

## 7. Declared performance:

| Essential Characteristics   | Unit   | Performance   | Class (group) |
|---|--------|---|---------------|
| Dimensions: length, width, height                                       | mm     | 250 x 120 x 88  |               |
| Dimensional Tolerances Category   | mm     | ±2 x ±2 x ±2  | T1            |
| Configuration group according to EC 6                                   |        |   | 1             |
|   |        | 250   |               |
| Compressive Strength:   |        | <sup>⊥</sup> to the bed surface of the intact product |               |
| Mean  | N/mm²  | ≥13,8   |               |
| Normalized  | N/mm²  | ≥10,0   | 10            |
| Shear bond strength, fixed value by LST EN 998-2                        |        |   |               |
| (annex C)   | N/mm²  | 0,15  |               |
| Reaction to fire  |        |   | A1            |
| Water absorption  | %      | ≤16   |               |
| Water vapour diffusion coefficient according to                         |        |   |               |
| LST EN 1745 (annex A)   |        | 5/25  |               |
| Direct airborne sound insulation:                                       |        |   |               |
| Gross dry density   | kg/m³  | 1710-1900   |               |
| Thermal conductivity $\lambda_{10,\text{dry,unit}}$ according to LST EN |        |   |               |
| 1745 (annex B)  | W/mK   | 0,92  |               |
| Durability against freeze-thaw  | Cycles | ≥ 50  | F2            |
| Dangerous substances  |        | None  |               |

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

nom!

Signed for and on behalf of the manufacturer by:

Vytautas Česnauskas, Director General

Vilnius, 2018-05-02